## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

1. (Currently amended) A user interface automation system comprising: an input component that receives a request; and,

a navigation component that receives the request from the input component and facilitates simulated user interface associated with an automation component based, at least in part, upon information stored in a map information store and information stored in a command information store, the navigation component further modifies the user interface automation without recompiling executables by modifying one or more of the map information store or the command information store, the navigation component further employs a global information store and facilitates a global variable replacement from a single location and sharing of a common program flow among a plurality of users.

- 2. (Original) The system of claim 1, wherein the automation component is a wizard.
- 3. (Original) The system of claim 1, wherein the map information store comprises a text-based file.
- 4. (Previously Presented) The system of claim 1, wherein the command information store comprises a text-based file.
- 5. (Cancelled)
- 6. (Previously Presented) The system of claim 1, the navigation component employing information stored in the global information store when a global variable is encountered in the command information store.

- 7. (Original) The system of claim 1, wherein at least one of the map information store and the configuration information store comprise at least one alias name.
- 8. (Original) The system of claim 1, wherein the navigation component further stores error information in a log information store.
- 9. (Original) The system of claim 1, wherein the navigation component further stores information associated with the request in a log information store.
- 10. (Original) The system of claim 9, wherein the navigation component iterates through information stored in the command information store, performs the indicated operation and stores information associated with the indicated operation in the log information store.
- 11. (Original) The system of claim 9, wherein the navigation component stores error information in the log information store.
- 12. (Original) The system of claim 1, wherein the input component performs input validation upon the request and provides error information if the request is invalid.
- 13. (Original) The system of claim 12, wherein a graphical message is displayed to a user of the system, the graphical message being based, at least in part, upon the error information from the input component.
- 14. (Original) The system of claim 1, wherein the input component receives a command line invocation.
- 15. (Original) The system of claim 1, the map information store comprising a section name and a page identifier.

- 16. (Original) The system of claim 15, the page identifier comprising a label for a control, the page identifier further uniquely identifying a particular page.
- 17. (Original) The system of claim 15, the page identifier comprising a control type.
- 18. (Original) The system of claim 17, wherein the control type is at least one of button, combo, list, scroll, static, radio and check.
- 19. (Original) The system of claim 1, wherein information stored in the command information store can be modified by at least one of a front-end user interface application, scripting, a batch file and a text editor.
- 20. (Original) The system of claim 1, the command information store comprising a section name, the section name corresponding to information stored in the map information store, the command information store further comprising an action.
- 21. (Original) The system of claim 1, the command information store storing information associated with at least one of a function key and a control key simulation.
- 22. (Previously Presented) A method of automating user interface comprising: receiving mapping information from a map information store; receiving command information from a command information store; retrieving global information from a global information store; performing simulated user interface based, at least in part, upon information stored in the map information store and the command information store; and modifying the user interface automation without recompilation of executables by storing data, commands and executables separately.
- 23. (Original) The method of claim 22, further comprising: storing information in a log information store, if an error is detected performing the simulated user interface.

- 24. (Original) A computer readable medium having stored thereon computer executable instructions for carrying out the method of claim 22.
- 25. (Currently amended) A method of automating user interface comprising:
  retrieving mapping information from a map file;
  retrieving command information from a command file;
  retrieving global information from a global file;
  obtaining a section name from the command file;
  retrieving page identification information from the map file associated with the section name;

retrieving section data for section associated with the section name from the command file;

performing an action associated with the retrieved section data; and sharing a common program flow among a plurality of users; and modifying the user interface automation without recompilation of executables by modifying the command file and/or map file.

- (Original) The method of claim 25, further comprising:storing information in a log file, if an error is detected performing the action.
- 27. (Original) A computer readable medium having stored thereon computer executable instructions for carrying out the method of claim 25.
- 28. (Currently amended) A user interface automation system comprising: an input component that receives a request; and,

a navigation component that receives the request from the input component and facilitates simulated user interface associated with an automation component based, at least in part, upon information stored in a map information store and information stored in a command information store, the navigation component further modifies the user interface automation without recompiling executables by modifying the map information store and/or the command information store, the navigation component further employs a

global information store and facilitates a global variable replacement from a single location and sharing of a common program flow among a plurality of users.

29. (Currently amended) A user interface automation system comprising: means for receiving a request;

means for simulating user interface associated with an automation component based, at least in part, upon information stored in a map information store and information stored in a command information store, the means for simulating receiving the request from the means for receiving; and

means for sharing a common program flow among a plurality of users based, at least in part, upon replacing a global variable in the command information store with corresponding data from a global information store; and

means for modifying the user interface automation without recompilation of executables.

30-32. (Canceled)

33. (Previously presented) The method of claim 22, wherein data and commands associated with program flow are stored in a text file.